

pep up RENOVIERFARBE FÜR MÖBEL, TÜREN & KÜCHENFRONTEN

Silk matt



1. Product features and field of application

“Turning old into wow”

SCHÖNER WOHNEN *pep up* – these trend-conscious interior renovation paints quickly and easily create a fresh look for your own four walls.

The *pep up* RENOVIERFARBE FÜR MÖBEL, TÜREN & KÜCHENFRONTEN is water-based, easy to apply, shock- and scratch-resistant and suitable for wood, melamine resin panels, pre-painted surfaces and bathroom furniture. Not suitable for worktops.

Color shade

According to current color card.

GISCODE
BSW30

Degree of gloss
Silk matt

Density
approx. 1.14 - 1.22 g/cm³

Composition

Urethane-acrylate-copolymer-dispersion, titanium dioxide (depending on the shade), inorganic/organic coloured pigments (depending on the shade), silicates, water, glycol ether, additives and preservatives (pyrithione zinc and benzisothiazolinone).

2. Use

Application techniques

(Roller, with a fine-pored foam roller), brush (with a plastic brush for water-dilutable paints).

Application temperature

Do not apply if air or object temperature is below +5°C.

Consumption

Approx. 90-125 ml/m² per layer (determine exact consumption value by means of a test application on the object to be coated)

Dilution

pep up RENOVIERFARBE FÜR MÖBEL, TÜREN & KÜCHENFRONTEN is ready for use and does not need to be diluted.

Tinting/mixing

All color shades can be mixed with one another.

Application information

Always stir well before use. Prepaint raw woods rich in active substances 1–2x times with a wood insulation primer. On difficult (e.g., very smooth) substrates or surfaces with a higher water load, we recommend applying a prime coat with the *pep up* GRUNDIERUNG FÜR RENOVIERFARBEN. Always apply the material quickly, thinly and wet-in-wet. We recommend 2 coats. Allow the paint to dry well between coats (approx. 8 hours). The surface can be fully stressed after approx. 7 days. Apply a protective coating with *pep up* VERSIEGELUNG FÜR RENOVIERFARBEN on surfaces subject to higher stresses. The degree of gloss of the surface can also be changed by using *pep up* VERSIEGELUNG FÜR RENOVIERFARBEN.

Care instructions

Spilled liquids must always be mopped up immediately. Standing water must be avoided.

Surfaces coated with pep up RENOVIERFARBE FÜR MÖBEL, TÜREN & KÜCHENFRONTEN may only be cleaned with commercially available abrasive-free cleaners with no warning labels. Clean only when slightly damp.

Drying time (at 20°C, 65% relative humidity)

Surface dry after approx. 1-2 hours, recoatable after approx. 8 hours. Fully cured for exposure to moisture after approx. 7 days. At lower temperatures and higher humidity the drying process takes longer.

Substrate preparation

Apply only to dry, clean, and firm substrates that are free of separating agents. Sand and thoroughly remove dust from new wood. Clean old (intact) coatings and rigid PVC, and sand well. Completely remove non-load-bearing, e.g., flaking coatings by sanding. Level out any unevenness in the interior with a spatula after priming.

Substrates	Priming	Top coat
Wood, melamine resin panels, pre-painted surfaces	If necessary, 1x pep up Grundierung	2x pep up RENOVIERFARBE FÜR MÖBEL, TÜREN, KÜCHENFRONTEN
Woods rich in active substances (e.g., oak, beech, cedar), Light top coat	1x wood insulation primer	

3. After application**Disposal**

Only recycle completely empty containers. Dispose of liquid material residue at a collection point for old paint/old varnishes according to Waste Code No. 080112 (in accordance with the Waste Catalog Ordinance (AVV)).

Tool cleaning

Clean the brush or roller immediately after use with lukewarm water and soap.

Storage/transport

Reseal opened containers tightly. Store in a cool and dry location.

Water pollution classification: WHC 1, in accordance with Administrative Regulation on the Classification of Substances Hazardous to Waters (AwSV)

4. Important notes

Standard protective measures must also be adhered to when applying pep up RENOVIERFARBE. Keep out of the reach of children. Use protective glasses and the combination filter A2/P2 for spraying. Use the dust filter P2 during sanding. Ensure proper ventilation during application and drying. Do not eat, drink or smoke while using the paint. Upon contact with the eyes or skin, immediately rinse thoroughly with water. Ensure that the material does not get into the sewage system, waters or soil.

Contains 1,2-BENZISOTHIAZOL-3(2H)-ONE. May produce an allergic reaction. Safety data sheet available upon request. Note! When spraying, dangerous respirable droplets can occur. Do not inhale the spray or mist.

Allergy hotline and other product information: 00800 32665500 (free).

EU limit value for this product (Cat. A/d): 130 g/l (2010). This product contains max. 100 g/l VOC.

5. General

All information and values are the products of extensive development activities and years of practical experience. Our spoken and written technical recommendations, which we prepare to support the buyer or user to the best of our knowledge on the basis of current information, do not constitute a contractual legal relationship. They do not release the buyer from his/her sole responsibility of assessing our products for suitability to the intended purpose. Our general terms and conditions also apply. The publication of a new version of this data sheet resulting from technical progress shall render all previous details invalid.

Last updated: December 2020